

ELECTRICAL KEY
 ALL ELECTRICAL WORK TO COMPLY WITH CURRENT IEE REGULATIONS
 AND PART II OF THE BUILDING STANDARDS (SCOTLAND) REGULATIONS 1990.
 ALL ELECTRICAL WORKS TO BE INSTALLED IN ACCORDANCE WITH BS 7671:1992

●	LIGHT SWITCH, No. OF WAYS INDICATED.
D+ (D+)	13A SINGLE SWITCHED SOCKET OUTLET. (& ABOVE WORKTOP)
D+ (D+)	13A DOUBLE SWITCHED SOCKET OUTLET. (& ABOVE WORKTOP)
D-	FUSED FLEX OUTLET.
D+	5 AMP CIRCUIT OUTLET
D+ (D+)	13A DOUBLE POLE SWITCH ABOVE WORKTOP WITH UNSWITCHED SOCKET BELOW.
○	PENDANT LIGHT FITTING WITH CEILING ROSE.
○	CEILING MOUNTED FLUORESCENT LIGHT FITTING WITH BATTEN AND INSTANT START GEAR.
○	RECESSED LOW VOLTAGE DOWNLIGHTER.
▽	WALL MOUNTED LIGHT FITTING.
⊕	EXTERNAL WALL MOUNTED LIGHT FITTING.
—	RADIATOR.
⊠	MECHANICAL EXTRACTOR FAN.
⊠	13A CONNECTION TO WATER HEATER.
SP	SHOWER POINT.
TV	TV AERIAL POINT.
TP	BT OUTLET.
ISDN	ISDN DIGITAL NETWORK OUTLET.
E	ELECTRICITY METER.
G	GAS METER.
⊠	ELECTRIC DISTRIBUTION BOARD.
⊠	INSTANTANEOUS ELECTRIC SHOWER WITH ANTI-SCALD VALVE
○	SURFACE MOUNTED INSULATED LIGHT FITTING.
SD	MAINS OPERATED SELF-CONTAINED SMOKE ALARM TO BS 5446 - PART 1 WIRED TO A SEPARATELY FUSED, LOW VOLTAGE CIRCUIT AT THE MAINS DISTRIBUTION BOARD VIA A MAINS TRANSFORMER. WHERE TWO OR MORE ALARMS ARE INSTALLED THEY SHALL BE INTERCONNECTED.
CMD	CARBON MONOXIDE DETECTOR
D+	SPUR FOR 3 kW ELECTRIC FIRE.
⊙	DOOR BELL PUSH
◀	DOOR BELL SOUNDER
P	CENTRAL HEATING PROGRAMMER
T	THERMOSTATIC CONTROL
ACU	APPLIANCE CONTROL UNIT
NOTE: POWER POINTS SHOWN BLACKENED WHEN LOCATED ABOVE WORKTOP HEIGHT.	

COPYRIGHT OF YEOMAN McALLISTER ARCHITECTS.


A & D. Brewster

HMO Application : 6 Coates Place

Existing Flat Layout Plan

JOB NO 007/8 DR NO SCALE NTS REV

YEOMAN McALLISTER
 COMPUTER AIDED DRAFTING



INCORPORATING
 HARLEY HADDOW ASSOCIATES
 Waterside Studios Coltbridge Avenue Edinburgh EH2 6AH 031-346-1145

Bedroom

St

Bathroom

St

Hall

Kitchen

CLIENT

JOB

DRAWIN

DRAWN